



**A** **EASY** **BF4C – BF4F**



Faretto led con attacco MR16, lente da 40°

*Spot led with MR16 plug, 40° lens*

CODE	V Dc	POWER W	PLUG	IP	COLOR	H x D mm	lm	TC °k	CRI
<b>BF4C</b>	12	6	MR16	44	WARM	45x50	350	3000	>80
<b>BF4F</b>	12	6	MR16	44	COLD	45x50	410	6000	>80



**A** **EASY** **BF5C - BF5N - BF5F**



Modulo AR111 a luce riflessa con un led COB apertura fascio 20°

*AR111 LED light reflection with one COB led beam angle 20°*

CODE	V dc	POWER W	N° LED	IP	COLOR	D mm	lm	TC °k	H mm
<b>BF5C</b>	12	15	1	20	WARM	111	780	3000	85
<b>BF5N</b>	12	15	1	20	NATUR	111	800	4500	85
<b>BF5F</b>	12	15	1	20	COLD	111	820	6000	85



**A** **BF6C - BF6N - BF6F**



Modulo AR111 a luce riflessa con un led COB apertura fascio 40°

*AR111 LED light reflection with one COB led beam angle 40°*

CODE	V dc	POWER W	N° LED	IP	COLOR	D mm	lm	TC °k	H mm
<b>BF6C</b>	12	17	1	20	WARM	111	1150	3000	85
<b>BF6N</b>	12	17	1	20	NATUR	111	1200	4500	85
<b>BF6F</b>	12	17	1	20	COLD	111	1250	6000	85